

imagePROGRAF TC-20 M

UNLOCK LARGE FORMAT POTENTIAL FROM SMALL SPACES

Ideal for offices, retail, travel agencies, education, AEC, etc.

Versatile functionality

Make use of an A4 flatbed scanner with enlarge, copy and repeat functions to create a range of output including educational material, flyers and personalised wrapping paper.

• Print in superior quality

High-quality pigment ink prints, without the price tag. Use the added scanning function and free PosterArtist app to produce professional prints of all sizes (including posters, flyers and menus) without relying on digital source files.

Smooth workflows

Easily set up roll paper with a shaftless roll holder and use the built-in auto-sheet feeder to keep prints moving without intervention. Print from a USB without PC operation and produce large format prints with the intuitive, easy-to-use scanning function.

Best office support

Brings more values than typical office devices — with scanning, copying and printing with cut sheets or roll paper, all-in-one. Besides printing standard documents, you can expand prints to large format like notifications and posters, up to A1 size.

Green at heart

Meet your sustainability goals with easily recyclable plastic 70ml ink bottles, reduced packaging and low energy consumption from an EPEAT Gold* rated device.



*EPEAT Gold registered in the U.S.

TECHNICAL SPECIFICATIONS

imagePROGRAF **TC-20 M**

Roll Paper: One roll Cut Sheet: 100 sheets (A4), 50 sheets (A3)

Desktop Basket (BU-06): Standard position - 1 sheet

Operation: 28W or less Sleep mode: 2.4W or less Default setting for the time to enter the Sleep mode:

PRINTER TECHNOLOGY Printer Type Print Technology

Print Resolution Number of Nozzles

Line Accuracy

Nozzle Pitch Ink Capacity

Ink Type **OS** Compatability

Printer Languages

Others supported job submission protocol Standard Interfaces

SCANNER TECHNOLOGY Scanner Type Scanner Resolution³ (Optical) Scanning Depth (Input/Output) Line Scanning speed

Maximum Document Size

MEMORY Standard memory

Hard Drive

DDINT SDEED CAD Drawing

Poster

MEDIA HANDLING Media Feed and Output

Media Width

Media Thickness Minimum Printable Length Maximum Printable Length

Maximum Media Roll Diameter Media Core Size Margins Recommended area

Margins Printable area





4 Colour 24" Canon Pigment ink 4 colours integrated type (4 chips per print head x 1 print head) 2,400 x 1,200 dpi Total : 4352 nozzles BK: 1280 nozzles C, M, Y : 1024 nozzles each

User adjustments necessary. Printing environment and media must match those used for the adjustments.

1.200 dpi x 2 lines Bundled Starter Ink: 280ml (70mlx4 for BK, C, M, Y) Sales Ink: 70ml (BK, C, M, Y) Pigment inks: 4 colour BK/C/M/Y

32 Bit: Windows7, Windows 8.1, Windows 10 64 Bit: Windows7, Windows 8.1, Windows 10, Windows 11, Windows Server 2008R2, 2012, 2012R2, 2016, 2019,2022 Apple Macintosh: macOS 10.14.6-macOS 12,x USB Memory Direct Print: PDF¹, JPEG (Exif ver2.2/2.21/2.3)

Apple AirPrint, Mopria, Chrome OS

USB A Port: USB Memory (Direct Print) - PDF¹/JPEG (Exif ver2.2/2.21/2.3) USB B Port: Hi-Speed USB Ethernet: IEEE802.3u(100BASE-TX) / IEEE802.3(10BASE-T) Wireless LAN²: IEEE802.11n/IEEE802.11g/IEEE802.11b

Flatbed CIS colour scanner Main scan X sub scan: 1200 x 2400 dpi Color: RGB each 16bit / each 8bit Greyscale: 16bit / 8bit Colour: 3.5 ms/line at 300 dpi Grayscale / Monochrome: 1.5 ms/line at 300 dpi A4/LTR(216 x 297mm)

1GB Expansion slot: No N/A

Plain paper (A1, B&W): 0:33 (Standard)

Plain Paper (A1, Colour): 1:03 (Standard) Plain Paper (A1)

1:10 (Fast) 2:08 (Standard) Coated Paper (A1) 3:10 (Fast) 6:05 (Standard)

Roll Paper: One Roll, Front-loading, Front Output Cut Sheet: Auto sheet feeder Roll paper : A3, A2, A2+, A1, B2, B3, 18", 24", 17" Cut sheet: 210mm - 297mm Roll/Cut : 0.08mm - 0.28mm Roll/Cut: 203.2mm Roll paper: 4m Cut sheet: 432mm 110mm

Internal diameter of roll core: 2" Roll paper: Top: 5mm, Bottom: 5mm, Side: 5mm (some photo mode: Top: 30mm, Bottom: 30mm) Cut sheet: Top: 5mm, Bottom: 5mm, Side: 5mm Roll paper: Top: 5mm, Bottom: 5mm, Side: 5mm (some photo mode: Top: 30mm, Bottom: 30mm) Cut sheet: Top: 5mm, Bottom: 5mm, Side: 5mm Media Feed Capacity Media Take-up roll unit

Borderless Printing Width (Roll Only) Maximum number of delivered prints

POWER AND OPERATING REQUIREMENTS Power Supply

Power Consumption

Operating Environment

Acoustic Noise (Pressure / Power)

Regulations Environment Certificates

DIMENSIONS AND WEIGHT Physical Dimensions and Weight

Packaged Dimensions and Weight

WHAT'S INCLUDED What's in the Box?

Software Included

OPTIONS **Optional Items**

CONSUMABLES User Replaceable Items

Footnotes

⁽¹⁾ PDF supports only files generated by imagePROGRAF TC-20M and Canon IJ Scan Utility

^[2] Please refer to user manual how to activate/deactivate the wireless LAN

⁽³⁾ Optical resolution is based on the ISO 14473 standard and represents the maximum sampling rate for scanning documents.

Disclaimer

Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice.²⁴ and ²⁶: All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see which variety of paper/media is recommended

Approx. 5 minutes Power off: 0.3W or less Temperature: 15~30°C, Humidity: 10~80% RH (no dew condensation) Operation: Approx. 41.5 dB(A) (Plain paper, Standard mode, Line Drawing/Text mode) Standby: 35 dB(A) or less (Measured on ISO 7779 standard)

CE mark, UKCA mark CB certfication. EPEAT GOLD⁴

AC 100-240V (50-60Hz)

N/A

N/A

W x D x H Main Unit 968 x 545 x 395 mm (ASF Opened) 968 x 525 x 245 mm (ASF Closed) 33 kg (exclude ink bottle, include print head)

Main Unit + Desktop Basket (BU-06) 968 x 825 x 965° mm (Basket Opened) 968 x 525 x 965° mm (Basket Closed) 34 kg (exclude ink bottle, include print head) "Height above which cloth does not touch the floor when op *Height above v

Main Unit + Stand + Basket (SD-24) 968 × 870 × 874 mm (Basket Opened) 968 × 707 × 874 mm (Basket Closed) 42 kg (exclude ink bottle, include print head)

Printer (Main unit): 1120 x 726 x 406 mm, 45kg Desktop Basket (BU-06): 798 x 301 x 111 mm, 1.8kg Stand + Basket (SD-24): 1055 x 824 x 268 mm, 16kg

Printer, 1 Print head, Power Cable, 1 Set of starter ink tanks, Installation Guide, Safety/Standard Environment leaflet, EU Biocide Sheet, LFP Eur Address Sheet, Flange protective materials sheet

Software available as Download from Web

Desktop Basket: BU-06 Printer Stand + Basket: SD-24

Ink Tank: PFI-050 (70ml) Print Head: PF-08 Maintenance Cartridge: MC-32

[4] EPEAT Gold registered in the U.S.

Canon Inc. canon.com Canon Europe canon-europe.com English edition © Canon Europa N.V.,2023

